

SAFETY DATA SHEET

Preparation Date: 9/27/2013

Revision Date: 9/17/2018

Revision Number: G8

1. IDENTIFICATION

Product identifier

Product code: ET107
Product Name: DEHYDRATED ALCOHOL, 200 PROOF, USP

Other means of identification

Synonyms: Absolute ethanol
Alcohol
Alcohol dehydrated
Alcohol, anhydrous
Alcool ethylique (French)
Absolute Ethanol 200 proof
Ethanol
Ethyl alcohol anhydrous
Ethyl hydrate
Ethyl hydroxide
Fermentation alcohol
Dehydrated Alcohol
Ethanol, undenatured 200 proof
Ethanol 200 proof
Ethyl alcohol
Alcohol etílico (Spanish)

CAS #: 64-17-5
RTECS # KQ630000
CI#: Not available

Recommended use of the chemical and restrictions on use

Recommended use: Solvent. Perfuming agent. In pharmaceuticals. Inks. In organic synthesis. In beverages.

Uses advised against No information available

Supplier: Spectrum Chemical Mfg. Corp
14422 South San Pedro St.
Gardena, CA 90248
(310) 516-8000

Order Online At: <https://www.spectrumchemical.com>

Emergency telephone number Chemtrec 1-800-424-9300

Contact Person: Martin LaBenz (West Coast)

Contact Person: Ibad Tirmiz (East Coast)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Considered a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Serious eye damage/eye irritation	Category 2
Reproductive toxicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Flammable liquids	Category 2

Label elements

Danger

Hazard statements
 Causes serious eye irritation
 May damage fertility or the unborn child
 May cause respiratory irritation. May cause drowsiness or dizziness
 Causes damage to organs through prolonged or repeated exposure
 Highly flammable liquid and vapor



Hazards not otherwise classified (HNOC)

Not Applicable

Other hazards

Can burn with an invisible flame
 Causes mild skin irritation

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Wash face, hands and any exposed skin thoroughly after handling
 Do not breathe dust/fume/gas/mist/vapors/spray
 Do not eat, drink or smoke when using this product
 Wear protective gloves/protective clothing/eye protection/face protection
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting/.../equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 In case of fire: Use CO2, dry chemical, or foam to extinguish.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
 If skin irritation occurs: Get medical advice/attention
 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Ethyl Alcohol 200 proof	64-17-5	100

4. FIRST AID MEASURES**First aid measures**

- General Advice:** National Capital Poison Center in the United States can provide assistance if you have a poison emergency and need to talk to a poison specialist. Call 1-800-222-1222.
- Skin Contact:** Wash off immediately with soap and plenty of water removing all contaminated clothing and shoes. Get medical attention. If skin irritation persists, call a physician.
- Eye Contact:** Flush eyes with water for 15 minutes. Get medical attention.
- Inhalation:** Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
- Ingestion:** Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician if necessary.

Most important symptoms and effects, both acute and delayed

- Symptoms**
- Causes eye irritation
 - May cause skin irritation
 - May cause irritation of respiratory tract
 - Dyspnea (Difficulty breathing and shortness of breath)
 - Central nervous system effects
 - Dizziness
 - Drowsiness
 - Headache
 - Ataxia
 - Staggering gait
 - Nausea
 - Vomiting
 - May cause cardiovascular effects

Indication of any immediate medical attention and special treatment needed

- Notes to Physician:** Treat symptomatically.

Protection of first-aiders

First-Aid Providers: Avoid exposure to blood or body fluids. Wear gloves and other necessary protective clothing. Dispose of contaminated clothing and equipment as bio-hazardous waste.

5. FIRE-FIGHTING MEASURES**Extinguishing Media**

- Suitable Extinguishing Media:** Carbon dioxide (CO₂). Dry chemical. Alcohol-resistant foam. Water spray.

- Unsuitable Extinguishing Media:** Do not use a solid (straight) water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Hazardous Combustion Products:

Carbon Monoxide, Carbon Dioxide.

Specific hazards:

Flammable. May be ignited by heat, sparks or flames. Material can burn with invisible flame. Vapor may travel considerable distance to source of ignition and flash back. Vapors may form explosive mixtures with air. Most vapors are heavier than air. They will spread along the ground and collect in low or confined areas (sewers, basements, tanks). Container explosion may occur under fire conditions or when heated. Fire may produce irritating, corrosive and/or toxic gases.

Special Protective Actions for Firefighters

Specific Methods:

Water mist may be used to cool closed containers. For larger fires, use water spray or fog. Cool containers with flooding quantities of water until well after fire is out.

Special Protective Equipment for Firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions:

Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition. Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use spark-proof tools and explosion-proof equipment. In case of large spill, water spray or vapor suppressing foam may be used to reduce vapors, but may not prevent ignition in closed spaces.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for containment

Stop leak if you can do it without risk. Absorb spill with inert material (e.g. vermiculite, dry sand or earth). In case of large spill, dike if needed. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up

Use appropriate tools to put the spilled material in a suitable chemical waste disposal container. Use only non-sparking tools. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Technical Measures/Precautions:

Provide sufficient air exchange and/or exhaust in work rooms. Remove all sources of ignition. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from incompatible materials.

Safe Handling Advice

Wear personal protective equipment. Use only in well-ventilated areas. Avoid contact with skin, eyes and clothing. Keep away from heat and sources of ignition. Do not breathe vapors or spray mist. Do not ingest. When using do not smoke. Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Technical Measures/Storage Conditions:

Keep container tightly closed in a dry and well-ventilated place. Store at room temperature in the original container. Sensitive to light. Store in light-resistant containers. Keep away from heat and sources of ignition. Store in a segregated and approved area. Store away from incompatible materials.

Incompatible Materials:

- Oxidizing agents
- Acids
- Alkali Metals
- Halogens
- Caustics
- isocyanates
- Metals
- Bases
- Acid anhydrides
- Acid chlorides

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

National occupational exposure limits

United States

Components	CAS-No.	OSHA	NIOSH	ACGIH	AIHA WEEL
Ethyl Alcohol 200 proof	64-17-5	1000 ppm TWA 1900 mg/m ³ TWA	1000 ppm TWA 1900 mg/m ³ TWA	1000 ppm STEL	None

Canada

Components	CAS-No.	Canada - Alberta	Canada - British Columbia	Canada - Ontario	Canada - Quebec
Ethyl Alcohol 200 proof	64-17-5	1000 ppm TWA 1880 mg/m ³ TWA	1000 ppm STEL	1000 ppm STEL	None

Australia and Mexico

Components	CAS-No.	Australia	Mexico
Ethyl Alcohol 200 proof	64-17-5	1000 ppm TWA 1880 mg/m ³ TWA	1000 ppm TWA 1900 mg/m ³ TWA

Appropriate engineering controls

Engineering measures to reduce exposure:

Ensure adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors and mist below their respective threshold limit value.

Individual protection measures, such as personal protective equipment

Personal Protective Equipment

Eye protection:	Goggles Safety glasses with side-shields.
Skin and body protection:	Chemical resistant apron Long sleeved clothing Gloves
Respiratory protection:	Vapor respirator. Be sure to use an approved/certified respirator or equivalent.
Hygiene measures:	Avoid contact with skin, eyes and clothing. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid	Appearance: No information available.	Color: Clear. Colorless.
Odor: Mild. Pleasant. Alcoholic. Like wine or whiskey. Ethereal.	Taste Pungent. Burning.	Formula: CH ₃ CH ₂ OH
Molecular/Formula weight (g/mole): 46.07	Flammability: No information available	Flashpoint (°C/°F): 12-14 °C/53.6-57.2 °F 15.8-18 °C/60.44-64.4 °F
Flash Point Tested according to: Closed cup Open cup	Autoignition Temperature (°C/°F): 363-426 °C/685.4-798.8 °F	Lower Explosion Limit (%): 3.3%
Upper Explosion Limit (%): 19%	Melting point/range(°C/°F): -114.1-117.3 °C/-173.38-179.14 °F	Decomposition temperature(°C/°F): No information available
Boiling point/range(°C/°F): 78-79 °C/172.4-174.2 °F	Bulk density: No information available	Density (g/cm³): No information available
Specific gravity: 0.789 @ 20 °C	pH: No information available	Vapor pressure @ 20°C (kPa): 5.7-5.866
Evaporation rate: No information available	Vapor density: 1.59	VOC content (g/L): 789
Odor threshold (ppm): 5-10 (recognition) 84 (tolerance)	Partition coefficient (n-octanol/water): -0.31	Viscosity: No information available
Miscibility: Miscible with water Miscible with Acetone Miscible with Ether Miscible with Benzene Miscible with glacial Acetic Acid Miscible with many organic solvents	Solubility: Very soluble in water Soluble in Benzene	

10. STABILITY AND REACTIVITY

Reactivity

When Ethanol comes in contact with Sodium, it liberates flammable hydrogen gas
It can react vigorously or explosively with acid hydrides or acid chlorides
It reacts with alkali metals to liberate flammable hydrogen gas
It reacts with acetyl bromide to evolve hydrogen bromide
It reacts with ammonia + silver nitrate to form silver nitride and silver fulminate
Ethyl alcohol can react with freshly cut/etched/scratched aluminum with the evolution of heat and release of hydrogen gas. The Ethyl alcohol has to be on the aluminum surface as it is being cut/scratched/etched

Ethyl Alcohol reacts vigorously with acetyl chloride.

Ethyl alcohol reacts with silver (I) oxide + ammonia or hydrazine to form silver nitride and silver fulminate

Ethanol ignites and then explodes on contact with the following compounds: acetic anhydride + sodium hydrosulfate, disulfuric acid + nitric acid, phosphorus (III) oxide, platinum, potassium tert-butoxide + acids

Ethanol rapidly absorbs moisture from the air. Can react vigorously/explosively with oxidizers. Ethanol can react vigorously/explosively with the following: ammonium hydroxide & silver oxide, chlorine or chlorine oxides, perchlorates (barium perchlorate, chloryl perchlorate, magnesium perchlorate (forms ethyl perchlorate), nitrosyl perchlorate, potassium perchlorate, silver perchlorate, uranyl perchlorate), acetic anhydride, acetyl bromide (evolves hydrogen bromide), acetyl chloride, aluminum sesquibromide ethylate, bromine pentafluoride, calcium hypochlorite, chromic anhydride, chromium trioxide, chromyl chloride, cyanuric acid + water, dichloromethane + sulfuric acid + nitrate (or) nitrite, manganese perchlorate + 2,2-dimethoxy propane, dioxygen difluoride, disulfuryl difluoride, fluorine nitrate, hydrogen peroxide, iodine heptafluoride, manganese heptoxide, iodine + methanol + mercuric oxide, iodine + Phosphorus (forms ethane iodide), mercuric nitrate, nitric acid, perchloric acid, permanganic acid, peroxodisulfuric acid, platinum black, potassium dioxide, potassium permanganate, potassium superoxide, potassium tert-butoxide, ruthenium(VIII) oxide, silver + nitric acid (forms silver fulminate), silver nitrate (forms ethyl nitrate), silver peroxide, sodium hydrazide, hydrogen peroxide + sulfuric acid, sulfuric acid + permanganates, uranium hexafluoride, sulfuric acid + sodium dichromate, tetrachlorosilane + water, silver & nitric acid, tetraphosphorus hexaoxide

Chemical stability

Stability: Stable under recommended storage conditions.

Possibility of Hazardous Reactions: Hazardous polymerization does not occur

Conditions to avoid: Heat. Ignition sources. Incompatible materials.

Incompatible Materials: Oxidizing agents
Acids
Alkali Metals
Halogens
Caustics
isocyanates
Metals
Bases
Acid anhydrides
Acid chlorides

Hazardous decomposition products: Carbon monoxide. Carbon dioxide. When heated to decomposition it emits acid smoke and irritating fumes.

Other Information

Corrosivity: No information available

Special Remarks on Corrosivity: No information available

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Principal Routes of Exposure:

Ingestion. Skin. Eyes. Inhalation.

Acute Toxicity

Component Information

Ethyl Alcohol 200 proof

CAS-No. 64-17-5

Product code: ET107

Product name: DEHYDRATED
ALCOHOL, 200 PROOF, USP

7 / 14

LD50/oral/rat = 7060 mg/kg Oral LD50 Rat
LD50/oral/mouse = 3450 mg/kg Oral LD50 Mouse
LD50/dermal/rabbit = No information available
LD50/dermal/rat = No information available
LC50/inhalation/rat = 124.7 mg/L Inhalation LC50 Rat 4 h
LC50/inhalation/mouse = 39000 mg/m³ 4 h
Other LD50 or LC50 information = >60000 ppm Inhalation LC50 Mouse 1 h
5900 mg/m³ Inhalation LC50 Rat 6 h
20000 ppm Inhalation LC50 Rat 10 h
5560 mg/kg Oral LD50 Guinea Pig
6300 mg/kg Oral LD50 Rabbit

Product Information

LD50/oral/rat =
VALUE- Acute Tox Oral = 7060 mg/kg

LD50/oral/mouse =
Value - Acute Tox Oral = 3450 mg/kg

LD50/dermal/rabbit
VALUE-Acute Tox Dermal = No information available

LD50/dermal/rat
VALUE -Acute Tox Dermal = No information available

LC50/inhalation/rat
VALUE-Vapor = 124.7 mg/l (4-hr)
VALUE-Gas = No information available
VALUE-Dust/Mist = No information available

LC50/Inhalation/mouse
VALUE-Vapor = 39 mg/l (4-hr)
VALUE - Gas = No information available
VALUE - Dust/Mist = No information available

Symptoms

Skin Contact: Mildly to moderately irritating to the skin.

Eye Contact: Causes serious eye irritation. Causes moderate to severe eye irritation.

Inhalation May cause irritation of respiratory tract. Symptoms may include coughing and shortness of breath. May cause nausea and headache. It may affect behavior/central nervous system (ataxia, general anesthetic, drowsiness). May affect respiration (respiratory depression). Inhalation of high concentrations of vapor may cause anesthetic effects. Inhalation of high concentrations of vapors may cause dizziness or suffocation. May affect the brain.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause gastritis. May cause loss of appetite. May cause flushed skin. May affect the cardiovascular system (change in heart rate). May affect the cardiovascular system (hypotension or hypertension, tachycardia, dysrhythmias). It may affect behavior/central nervous system (excitation, mild euphoria, excessive talking, fatigue, headache, dizziness, drowsiness, staggering gait, ataxia, hallucinations, slurred speech, amnesia, confusion, release of inhibitions, aggressive behavior, convulsions, coma). May affect respiration (dyspnea, respiratory depression). It may affect the brain. May affect liver. May affect the blood. May affect the

endocrine system. It may affect the spleen. May affect urinary system (kidneys).

Aspiration hazard No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity Prolonged or repeated skin contact may cause dermatitis, and dryness and cracking of the skin. Prolonged or repeated ingestion may affect behavior/central nervous system. Prolonged or repeated ingestion may affect metabolism (cause anorexia, weight loss). Prolonged or repeated ingestion may affect the liver (fatty liver degeneration, cirrhosis of the liver. Prolonged or repeated ingestion may affect the cardiovascular system. Prolonged or repeated inhalation may affect the liver.

Sensitization: No information available.

Mutagenic Effects: May affect genetic material based on animal test data
 Mutations in microorganisms
 Experiments with bacteria and/or yeast have shown mutagenic effects
 Cytogenic analysis - hamster ovary
 Cytogenic Analysis (Hamster embryo)
 Cytogenic analysis - human leukocyte
 Cytogenic Analysis: human lymphocyte
 Sister Chromatid Exchange - Hamster ovary
 Sister Chromatid Exchange (human lymphocyte)

Carcinogenic effects: Equivocal tumorigenic agent by Registry of Toxic Effects of Chemical Substances (RTECS) criteria. Confirmed Animal Carcinogen with Unknown Relevance to Humans.

Components	CAS-No.	IARC	ACGIH - Carcinogens	NTP	OSHA HCS - Carcinogens	Australia - Notifiable Carcinogenic Substances	Australia - Prohibited Carcinogenic Substances
Ethyl Alcohol 200 proof	64-17-5	Group 1 - Monograph 100E [2012] in alcoholic beverages Monograph 96 [2010] in alcoholic beverages	A3 Confirmed Animal Carcinogen with Unknown Relevance to Humans	Not listed	Present	Not listed	Not listed

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

(In alcoholic beverages)

NTP (National Toxicology Program)

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

Reproductive toxicity May damage fertility or the unborn child

Reproductive Effects: Causes adverse reproductive effects
Developmental Effects: May cause harm to the unborn child
 May cause adverse developmental effects
Teratogenic Effects: Causes birth defects (teratogenic effects)

Specific Target Organ Toxicity

STOT - single exposure
STOT - repeated exposure
Target Organs:

Respiratory system. central nervous system.
Causes damage to organs through prolonged or repeated exposure.
Skin. Liver. Central nervous system. Nervous system. Heart. Reproductive System.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Ecotoxicity effects: Aquatic environment.

Ethyl Alcohol 200 proof - 64-17-5

Freshwater Fish Species Data: 12.0 - 16.0 mL/L LC50 *Oncorhynchus mykiss* 96 h static 1 100 mg/L LC50 *Pimephales promelas* 96 h static 1 13400 - 15100 mg/L LC50 *Pimephales promelas* 96 h flow-through 1

Water Flea Data: 9268 - 14221 mg/L LC50 *Daphnia magna* 48 h 2 mg/L EC50 *Daphnia magna* 48 h 10800 mg/L EC50 *Daphnia magna* 24 h

Persistence and degradability: No information available

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Disposal Methods

Waste from residues / unused products:

Waste must be disposed of in accordance with Federal, State and Local regulation.

Contaminated packaging:

Empty containers should be taken for local recycling, recovery or waste disposal

Components	CAS-No.	RCRA - F Series Wastes	RCRA - K Series Wastes	RCRA - P Series Wastes	RCRA - U Series Wastes
Ethyl Alcohol 200 proof	64-17-5	None	None	None	None

14. TRANSPORT INFORMATION

DOT

UN-No: UN1170
Proper Shipping Name: Ethanol
Hazard Class: 3
Subsidiary Class No information available
Packing group: II
Emergency Response Guide Number 127
Marine Pollutant No data available
DOT RQ (lbs): No information available
Special Provisions 24, IB2, T4, TP1
Symbol(s): No information available
Description: UN1170, Ethanol, 3, II

TDG (Canada)

UN-No: UN1170

Product code: ET107

Product name: DEHYDRATED
ALCOHOL, 200 PROOF, USP

10 / 14

Proper Shipping Name: Ethanol
Hazard Class: 3
Subsidiary Risk: No information available
Packing Group: II
Marine Pollutant Description: No Information available
UN1170, Ethanol, 3, II

ADR

UN-No: UN1170
Proper Shipping Name: Ethanol
Hazard Class: 3
Packing Group: II
Subsidiary Risk: No information available
Special Provisions Description: 144, 601
UN1170, Ethanol, 3, II

IMO / IMDG

UN-No: UN1170
Proper Shipping Name: Ethanol
Hazard Class: 3
Subsidiary Risk: No information available
Packing Group: II
Marine Pollutant Description: No information available
EMS: F-E
Special Provisions Description: 144
UN1170, Ethanol, 3, II

RID

UN-No: UN1170
Proper Shipping Name: Ethanol
Hazard Class: 3
Subsidiary Risk: 3
Packing Group: II
Special Provisions Description: 144, 601
UN1170, Ethanol, 3, II

ICAO

UN-No: UN1170
Proper Shipping Name: Ethanol
Hazard Class: 3
Subsidiary Risk: No information available
Packing Group: II
Description: UN1170, Ethanol, 3, II
Special Provisions: A58, A180, A3

IATA

UN-No: UN1170
Proper Shipping Name: Ethanol
Hazard Class: 3
Subsidiary Risk: No information available
Packing Group: II
ERG Code: 3L
Special Provisions Description: No information available
UN1170, Ethanol, 3, II

15. REGULATORY INFORMATION

International Inventories

Components	CAS-No.	U.S. TSCA	KOREA KECL	Philippines (PICCS)	Japan ENCS	CHINA	Australia (AICS)	EINECS-No.
Ethyl Alcohol 200 proof	64-17-5	Present(ACTI VE)	KE-13217	Present	(2)-202	Present	Present	Present 200-578-6

U.S. Regulations

Ethyl Alcohol 200 proof

Massachusetts RTK: Present

New Jersey RTK Hazardous Substance List: 0844

Pennsylvania RTK: Present

Minnesota - Hazardous Substance List: Present

Louisiana Reportable Quantity List for Pollutants: Present (listed as Volatile Organic Compounds)


California Directors List of Hazardous Substances: Present

FDA - Food Additives Generally Recognized as Safe (GRAS): 21 CFR 184.1293


FDA - 21 CFR - Total Food Additives 169.175, 169.176, 169.177, 169.181, 172.340, 172.560, 172.580, 175.105, 176.180, 176.200, 177.1200, 177.1650, 178.1010, 184.1293, 73.30, 73.345, 73.615

California Prop. 65: Safe Drinking Water and Toxic Enforcement Act of 1986.

Chemicals Known to the State of California to Cause Cancer:

 WARNING: This product can expose you to chemicals including (see table below) which is (are) known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Chemicals Known to the State of California to Cause Reproductive Toxicity:

 WARNING: This product can expose you to chemicals including (see table below) which is (are) known to the State of California to cause birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.

Components	CAS-No.	Carcinogen	Developmental Toxicity	Male Reproductive Toxicity	Female Reproductive Toxicity:
Ethyl Alcohol 200 proof	64-17-5	carcinogen (Ethanol in alcoholic beverages)	developmental toxicity (Ethyl alcohol in alcoholic beverages)	Not Listed	Not Listed

CERCLA/SARA

Components	CAS-No.	CERCLA - Hazardous Substances and their Reportable Quantities	Section 302 Extremely Hazardous Substances and TPQs	Section 302 Extremely Hazardous Substances and RQs	Section 313 - Chemical Category	Section 313 - Reporting de minimis
Ethyl Alcohol 200 proof	64-17-5	None	None	None	None	None

U.S. TSCA

Components	CAS-No.	TSCA Section 5(a)2 - Chemicals With Significant New Use Rules (SNURS)	TSCA 8(d) -Health and Safety Reporting
Ethyl Alcohol 200 proof	64-17-5	Not Applicable	Not Applicable

Canada

WHMIS 2015 - GHS Classifications

WHMIS 2015 Hazard Classification Information:

Component
Ethyl Alcohol 200 proof
64-17-5 (100)

WHMIS 2015 Hazard Classification
Flammable liquids - Category 2: H225 Highly flammable liquid and vapour.; Serious Eye Damage/Eye Irritation - Category 2B: H320

Product code: ET107

Product name: DEHYDRATED
ALCOHOL, 200 PROOF, USP

12 / 14

Causes eye irritation.

Canada Hazardous Products Regulation This product has been classified according to the hazard criteria of the HPR (Hazardous Products Regulation) and the SDS contains all of the information required by the HPR

Components	WHMIS Ingredient Disclosure List -
Ethyl Alcohol 200 proof	0.1 %

Inventory

Components	CAS-No.	Canada (DSL)	Canada (NDSL)
Ethyl Alcohol 200 proof	64-17-5	Present	Not Listed

Components	CAS-No.	CEPA Schedule I - Toxic Substances
Ethyl Alcohol 200 proof	64-17-5	Not listed
Components	CAS-No.	CEPA - 2010 Greenhouse Gases Subject to Mandatory Reporting
Ethyl Alcohol 200 proof	64-17-5	Not listed

EU Classification

EU GHS - SV - CLP 1272/2008

Components	CAS-No.	EU GHS - SV - CLP (1272/2008)
Ethyl Alcohol 200 proof	64-17-5	Flammable liquids - Flam. Liq. 2: H225 Highly flammable liquid and vapour.603-002-00-5

EU - CLP (1272/2008)

R-phrases

R11 - Highly flammable.

S-phrases

S 7 - Keep container tightly closed.

S16 - Keep away from sources of ignition - No smoking.

Components	CAS-No.	Classification	Concentration Limits:	Safety Phrases
Ethyl Alcohol 200 proof	64-17-5	F; R11	No information	S(2) S7 S16

The product is classified in accordance with Annex VI to Directive 67/548/EEC

Indication of danger:

F - Highly flammable.

F



16. OTHER INFORMATION

Preparation Date: 9/27/2013
Revision Date: 9/17/2018
Prepared by: Sonia Owen

Product code: ET107

Product name: DEHYDRATED
ALCOHOL, 200 PROOF, USP

13 / 14

Disclaimer:

All chemicals may pose unknown hazards and should be used with caution. This Safety Data Sheet (SDS) applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this SDS. The physical properties reported in this SDS are obtained from the literature and do not constitute product specifications. Information contained herein does not constitute a warranty, whether expressed or implied, as to the safety, merchantability or fitness of the goods for a particular purpose. Spectrum Chemicals & Laboratory Products, Inc. assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this SDS is based on technical data judged to be reliable, Spectrum assumes no responsibility for the completeness or accuracy of the information contained herein.

End of Safety Data Sheet