



SAFETY DATA SHEET

Preparation Date: 1/15/2014 Revision Date: 4/04/2018 Revision Number: G4

1. IDENTIFICATION

Product identifier

Product code: HP402

Product Name: ACETONE, EXCEEDS A.C.S. SPECIFICATIONS, HPLC GRADE

Other means of identification

Synonyms: beta-Ketopropane

Dimethyl ketone

Dimethylformaldehyde

Dimethylketal Ketone propane Ketone, dimethyl Methyl ketone Propanone Pyroacetic acid Pyroacetic ether Acétone (French)

Acetona (Spanish)

 CAS #:
 67-64-1

 RTECS #
 AL3150000

 CI#:
 Not available

Recommended use of the chemical and restrictions on use

Recommended use: Solvent.

Uses advised against No information available

Supplier: Spectrum Chemical Mfg. Corp

14422 South San Pedro St. Gardena, CA 90248

(310) 516-8000

Order Online At: https://www.spectrumchemical.com

Emergency telephone numberChemtrec 1-800-424-9300Contact Person:Martin LaBenz (West Coast)Contact Person:Ibad Tirmiz (East Coast)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Considered a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Serious eye damage/eye irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3

Flammable liquids Category 2

Label elements

Danger

Hazard statements

Causes serious eve irritation

Suspected of damaging fertility or the unborn child

May cause respiratory irritation. May cause drowsiness or dizziness

Highly flammable liquid and vapor



Hazards not otherwise classified (HNOC)

Not Applicable

Other hazards

Causes mild skin irritation

Repeated exposure may cause skin dryness or cracking

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/.../equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

In case of fire: Use CO2, dry chemical, or foam to extinguish.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Product name: ACETONE, EXCEEDS A.C.S. SPECIFICATIONS, HPLC GRADE

Components	CAS-No.	Weight %
Acetone	67-64-1	99-100.5
Benzene	71-43-2	0-0.003
Formaldehyde	50-00-0	0-0.002

4. FIRST AID MEASURES

First aid measures

General Advice: National Capital Poison Center in the United States can provide assistance if you

have a poison emergency and need to talk to a poison specialist. Call

1-800-222-1222.

Skin Contact: Wash off immediately with soap and plenty of water removing all contaminated clothing and

shoes. Get medical attention. If skin irritation persists, call a physician.

Eye Contact: Flush eyes with water for 15 minutes. Get medical attention.

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial

respiration. Get medical attention.

Ingestion: Do not induce vomiting without medical advice. Never give anything by mouth to an

unconscious person. Consult a physician if necessary.

Most important symptoms and effects, both acute and delayed

Symptoms Moderate eye irritation

Mild skin irritation

Nausea Vomiting

Central nervous system effects

Dizziness Drowsiness Fatigue Narcosis Ataxia Staggering gait

Headache

May affect respiration Respiratory depression

May cause cardiovascular effects

Hypotension

Weak, rapid pulse or rapid heart rate (Tachycardia)

May cause metabolic acidosis

Indication of any immediate medical attention and special treatment needed

Notes to Physician: Treat symptomatically.

Protection of first-aiders

First-Aid Providers: Avoid exposure to blood or body fluids. Wear gloves and other necessary protective clothing. Dispose of contaminated clothing and equipment as bio-hazardous waste.

5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Carbon dioxide (CO2). Dry chemical. Alcohol-resistant

foam. Water spray.

3 / 18

Unsuitable Extinguishing Media: Do not use a solid (straight) water stream as it may scatter

and spread fire.

Specific hazards arising from the chemical

Hazardous Combustion Products: Carbon Monoxide, Carbon Dioxide.

Specific hazards: Flammable. May be ignited by heat, sparks or flames.

Vapor may travel considerable distance to source of ignition and flash back. Vapors may form explosive mixtures with air. Most vapors are heavier than air. They will spread along the ground and collect in low or confined areas (sewers, basements, tanks). Container explosion may occur under fire conditions or when heated. Fire may

produce irritating, corrosive and/or toxic gases.

Special Protective Actions for Firefighters

Specific Methods: Water mist may be used to cool closed containers. For

larger fires, use water spray or fog. Cool containers with flooding quantities of water until well after fire is out.

Special Protective Equipment for Firefighters: As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions: Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid

contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition. Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use spark-proof tools and explosion-proof equipment. In case of large spill, water spray or vapor suppressing foam may be used to reduce vapors, but may not prevent ignition in closed

spaces.

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering

drains. Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Absorb spill with inert material (e.g.

vermiculite, dry sand or earth). In case of large spill, dike if needed. Dike far

ahead of liquid spill for later disposal.

Methods for cleaning upUse appropriate tools to put the spilled material in a suitable chemical waste

disposal container. Use only non-sparking tools. Clean contaminated surface

thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Technical Measures/Precautions:

Provide sufficient air exchange and/or exhaust in work rooms. Remove all sources of ignition. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from

Product code: HP402 Product name: ACETONE, EXCEEDS 4 / 18

incompatible materials.

Safe Handling Advice

Wear personal protective equipment. Use only in well-ventilated areas. Avoid contact with skin, eyes and clothing. Keep away from heat and sources of ignition. Do not breathe vapors or spray mist. Do not ingest. When using do not smoke. Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Technical Measures/Storage Conditions:

Keep container tightly closed in a dry and well-ventilated place. Store at room temperature in the original container. Keep away from heat and sources of ignition. Store in a segregated and approved area. Store away from incompatible materials.

Incompatible Materials:

Oxidizing agents

Reducing agents

Bases

Acids

activated carbon

chromium trioxide

dioxygen difluoride + carbon dioxide

Potassium dichromate or Sodium dichromate

Potassium t-butoxide

Hydrogen peroxide

Chromic anhydride

Chromyl chloride

Hexachloromelamine

Nitrosyl chloride + Platinum

Nitrosyl chloride

Bromine trifluoride

Thiodiglycol

2,4,6-trichloro-1,3,5-triazine + water

2-Methyl-1,3-butadiene

Chloroform

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

National occupational exposure limits

United States

Components	CAS-No.	OSHA	NIOSH	ACGIH	AIHA WEEL
Acetone	67-64-1	1000 ppm TWA	250 ppm TWA	750 ppm STEL	None
		2400 mg/m ³ TWA	590 mg/m ³ TWA	500 ppm TWA	
Benzene	71-43-2	10 ppm TWA	0.1 ppm TWA	2.5 ppm STEL	None
		1 ppm TWA	1 ppm STEL	0.5 ppm TWA	
		25 ppm Ceiling			
		5 ppm STEL			
Formaldehyde	50-00-0	0.75 ppm TWA	0.016 ppm TWA	0.3 ppm Ceiling	None
		2 ppm STEL	0.1 ppm Ceiling 15 min	-	

Canada

Components	CAS-No.	Canada - Alberta	Canada - British Columbia	Canada - Ontario	Canada - Quebec
Acetone	67-64-1	500 ppm TWA	250 ppm TWA	500 ppm TWA	500 ppm TWAEV

		1200 mg/m³ TWA 750 ppm STEL 1800 mg/m³ STEL	500 ppm STEL	750 ppm STEL	1190 mg/m³ TWAEV 1000 ppm STEV 2380 mg/m³ STEV
Benzene	71-43-2	0.5 ppm TWA 1.6 mg/m³ TWA 2.5 ppm STEL 8 mg/m³ STEL	0.5 ppm TWA 2.5 ppm STEL	0.5 ppm TWA 2.5 ppm STEL	1 ppm TWAEV 3 mg/m³ TWAEV 5 ppm STEV 15.5 mg/m³ STEV
Formaldehyde	50-00-0	1 ppm Ceiling 1.3 mg/m³ Ceiling 0.75 ppm TWA 0.9 mg/m³ TWA	0.3 ppm TWA 1 ppm Ceiling	1.5 ppm Ceiling 1.0 ppm STEL	2 ppm Ceiling 3 mg/m³ Ceiling

Australia and Mexico

Components	CAS-No.	Australia	Mexico
Acetone	67-64-1	1000 ppm STEL	1000 ppm TWA
		2375 mg/m ³ STEL	2400 mg/m³ TWA
		1185 mg/m³TWA	1260 ppm STEL
		500 ppm TWA	3000 mg/m ³ STEL
Benzene	71-43-2	1.0 ppm//3.2 mg/m ³ TWA	1 ppm TWA
		confirmed carcinogen	3.2 mg/m³ TWA
			5 ppm STEL
			16 mg/m ³ STEL
Formaldehyde	50-00-0	1 ppm/1.2 mg/m³ TWA	2 ppm Ceiling
		2 ppm/2.5 mg/m ³ STEL	3 mg/m³ Ceiling
		probable carcinogen	

Appropriate engineering controls

Engineering measures to reduce exposure: Ensure adequate ventilation. Provide exhaust ventilation or

other engineering controls to keep the airborne

concentrations of vapors and mist below their respective

threshold limit value.

Individual protection measures, such as personal protective equipment

Personal Protective Equipment

Eye protection: Goggles

Skin and body protection: Chemical resistant apron

Long sleeved clothing

Gloves

Respiratory protection: Vapor respirator. Be sure to use an approved/certified respirator or equivalent.

Hygiene measures: Avoid contact with skin, eyes and clothing. When using, do not eat, drink or

smoke. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Appearance: Color:

Liquid No information available. Clear. Colorless.

Odor:TasteFormula:Fruity. Mint-like. Fragrant. Ethereal.Pungent. Sweetish.C3-H6-O

Molecular/Formula weight: Flammability: Flash point (°C):

58.08 No information available -20 °C

Product code: HP402 Product name: ACETONE, EXCEEDS

A.C.S. SPECIFICATIONS, HPLC

Flashpoint (°C/°F): Flash Point Tested according to: Autoignition Temperature (°C/°F): 465 °C/869 °F

-20 to -17 °C/-4 to 1.4 °F Closed cup -9.4 to -9 °C/15.1 to 15.8 °F Open cup

Lower Explosion Limit (%): Upper Explosion Limit (%): Melting point/range(°C/°F):

-94.7 to -95.4 °C/-138.46 to -139.72 2.5-2.6% 12.8%

Decomposition temperature(°C/°F): Boiling point/range(°C/°F): Bulk density:

No information available 56.2 °C/133.2 °F No information available

Density (g/cm3): Specific gravity: pH:

0.780 @ 30 °C 0.784 @ 25 °C 0.79 @ 20 °C

0.79 @ 20 °C No information available

Vapor pressure @ 20°C (kPa): **Evaporation rate:** Vapor density:

5.6 (Butyl acetate = 1)

VOC content (g/L): Odor threshold (ppm): Partition coefficient 780-790 62-140 (n-octanol/water):

-0.24

Viscosity: Miscibility: Solubility:

No information available Miscible with water No information available

> Miscible with Ether Miscible with Chloroform Miscible with Benzene Miscible with alcohol

10. STABILITY AND REACTIVITY

Reactivity

Reactive with oxidizing agents Reacts with reducing agents

Reactive with acids

Reacts with strong bases

Acetone ignites on contact with activated carbon, chromium trioxide, dioxygen difluoride + carbon dioxide, potassium-tert-butoxide, sulfuric acid + potassium dichromate

Acetone may form explosive mixtures with chromic anhydride, chromyl chloride, hexachloromelamine, hydrogen peroxide, nitric acid and acetic acid, nitric acid and sulfuric acid, nitrosyl chloride, nitrosyl chloride + platinum, nitrosyl perchlorate, nitryl perchlorate, permonosulfuric acid, potassium tert-butoxide, thiodiglycol, chloroform, bromine trifluoride, thiotrithiazyl perchlorate, 2,4,6-trichloro-1,3,5-triazine + water, 2-methyl-1,3-butadiene, peroxomonosulfuric acid

An explosion occurred during an attempt to prepare bromoform from acetone by the haloform reaction

Chloroform and acetone interact vigorously and exothermally in presence of solid potassium hydroxide or calcium hydroxide to form 1,1,1-trichloro-2-hydroxy-2-methylpropane

Chemical stability

Stable under recommended storage conditions. Stability:

Possibility of Hazardous Reactions: Hazardous polymerization does not occur

Conditions to avoid: Heat. Ignition sources. Incompatible materials.

Incompatible Materials: Oxidizing agents

Reducing agents

Bases Acids

activated carbon chromium trioxide

Product code: HP402 Product name: ACETONE, EXCEEDS

A.C.S. SPECIFICATIONS, HPLC

7/18

dioxygen difluoride + carbon dioxide

Potassium dichromate or Sodium dichromate

Potassium t-butoxide
Hydrogen peroxide
Chromic anhydride
Chromyl chloride
Hexachloromelamine
Nitrosyl chloride + Platinum

Nitrosyl chloride Bromine trifluoride

Thiodiglycol

2-Methyl-1,3-butadiene

Chloroform

Hazardous decomposition

products:

Carbon monoxide. Carbon dioxide.

2,4,6-trichloro-1,3,5-triazine + water

Other Information

Corrosivity: No information available

Special Remarks on Corrosivity: No information available

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Principal Routes of Exposure:

Ingestion. Skin. Eyes. Inhalation.

Acute Toxicity

Component Information

Acetone		
CAS-No.	67-64-1	

LD50/oral/rat = 5800 mg/kg Oral LD50 Rat

LD50/oral/mouse = 3 gm/kg

LD50/dermal/rabbit = No information available

LD50/dermal/rat = No information available

LC50/inhalation/rat = 50100 mg/m³ Inhalation LC50 Rat 8 h

LC50/inhalation/mouse = 44 gm/m³/4H

Other LD50 or LC50information = >9400 uL/kg LD50 Dermal Guinea Pig

5340 mg/kg LD50 Oral Rabbit

Benzene

CAS-No. 71-43-2

LD50/oral/rat = 810 mg/kg Oral LD50 Rat = 1800 mg/kg Oral LD50 Rat; 930-6400 mg/kg (RTECS)

LD50/oral/mouse = 4700 mg/kg

LD50/dermal/rabbit = >9400 mg/kg Dermal LD50 Rabbit (RTECS)

>8200 mg/kg (LOLI)

LD50/dermal/rat = No information available

LC50/inhalation/rat = 13050 - 16000 ppm Inhalation LC50 Rat 4 h (EU Commission IUCLID dataset)

44.66 mg/L Inhalation LC50 Rat 4 h (LOLI)

LC50/inhalation/mouse = No information available

Other LD50 or LC50information = >9400 ul/kg LD50 Guinea Pig

Product code: HP402 Product name: ACETONE, EXCEEDS
A.C.S. SPECIFICATIONS, HPLC
GRADE

Formaldehyde

CAS-No. 50-00-0

LD50/oral/rat = 500 mg/kg Oral LD50 Rat (RTECS and LOLI)

100 mg/kg (RTECS)

LD50/oral/mouse = 500 mg/kg (RTECS)

385 mg/kg (RTECS) 42 mg/kg (RTECS)

LD50/dermal/rabbit = 270 mg/kg Dermal LD50Rabbit

LD50/dermal/rat = No information available

LC50/inhalation/rat = 0.578 mg/L Inhalation LC50 Rat 4 h

LC50/inhalation/mouse = No information available

Other LD50 or LC50information = 260 mg/kg oral LD50 Guinea Pig

Product Information

LD50/oral/rat =

VALUE- Acute Tox Oral = 5800

LD50/oral/mouse =

Value - Acute Tox Oral = 3000 mg/kg

LD50/dermal/rabbit

VALUE-Acute Tox Dermal = 20000 mg/kg

LD50/dermal/rat

VALUE -Acute Tox Dermal = No information available

LC50/inhalation/rat

VALUE-Vapor = 76 mg/l (4-hr)

VALUE-Gas = No information available

VALUE-Dust/Mist = No information available

LC50/Inhalation/mouse

VALUE-Vapor = No information available

VALUE - Gas = No information available

VALUE - Dust/Mist = No information available

Symptoms

Skin Contact: May cause skin irritation. Mildly to moderately irritating to the skin. It may be

absorbed through the skin. If absorbed through skin it may cause systemic effects

with symptoms similar to those of ingestion.

Eye Contact: Causes eye irritation. Moderately irritating to the eyes. May cause corneal injury.

Inhalation Irritating to respiratory system. May cause conjunctival irritation. May cause

nausea, vomiting. May cause loss of appetite. May affect the brain. May affect the

kidneys. May cause muscle weakness. May affect respiration (respiratory depression). Inhalation of high concentrations may cause central nervous system

effects characterized by headache, dizziness, unsteady gait, drowsiness, lethargy, sleepiness lightheadedness, fainting, narcosis, confusion, loss of coordination, lassitude, speech abnormalities, tremor, unconciousness, coma. May cause metabolic acidosis. May cause other symptoms similar to those of

ingestion.

Ingestion May cause digestive (gastointestinal) tract irritation. Ingestion may cause nausea,

vomiting. It may affect metabolism (ketosis/ketonemia/ketonuria). May cause

9/18

hyperglycemia. May affect liver. May affect respiration. May affect the cardiovascular system (hypotension). May affect the cardiovascular system (weak rapid pulse, tachycardia). May cause metabolic acidosis. May affect urinary system (kidneys). It may affect the joints. It may affect the skeletal muscles. It may affect behavior/central nervous system (depression, headache, tremors, ataxia, hyperesthesia, stupor, sedation, fatigue, excitement, seizures, coma).

Aspiration hazard

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity

Prolonged or repeated skin contact may cause defatting and drying of the skin, and brittle nails. Prolonged or repeated inhalation may affect the brain. Prolonged or repeated inhalation may affect the blood (changes in red blood cell count, granulocytopenia). Prolonged or repeated inhalation may affect the cardiovascular system. Prolonged or repeated inhalation may affect the thyroid (evidence of thyroid hyperfunction). Prolonged or repeated ingestion may affect the spleen. Prolonged or repeated ingestion may affect the bladder. Prolonged or repeated ingestion may affect the liver, and kidneys. Prolonged or repeated ingestion may affect the blood (normocytic anemia, macrocytosis). Prolonged or repeated inhalation may cause eve and throat irritation and bronchitis. Prolonged or repeated inhalation may cause nausea, gastritis, loss of appetite, and weight loss. Prolonged or repeated inhalation may cause central nervous system effects such

as weakness, dizziness, drowsiness, and vertigo.

Sensitization: No information available.

Mutagenic Effects: May affect genetic material

Sex Chromosome Loss and Nondisjunction in Saccharomyces cerevisiae (yeast)

Cytogenetic analysis (Hamster fibroblast)

Carcinogenic effects: Not classifiable as a human carcinogen.

Components	CAS-No.	IARC	ACGIH - Carcinogens	NTP	OSHA HCS - Carcinogens	Australia - Notifiable Carcinogenic Substances	Australia - Prohibited Carcinogenic Substances
Acetone	67-64-1	Not listed	A4 Not Classifiable as a Human Carcinogen	Not listed	Not listed	Not listed	Not listed
Benzene	71-43-2	Monograph 100F [2012] Supplement 7 [1987] Monograph 29 [1982]	A1 Confirmed Human Carcinogen	Known Human Carcinogen		Present includes pure substance or mixtures containing >=0.1% (w/w) concentration. Restricted use: all uses involving Benzene as a feedstock containing >50% of Benzene by volume;genuin e research or analysis	Not listed
Formaldehyde	50-00-0	Group 1 - Carcinogenic to Humans -	A2 Suspected Human Carcinogen	Known Human Carcinogen	Present see 29 CFR 1910.1048		Not listed

Product code: HP402 Product name: ACETONE, EXCEEDS A.C.S. SPECIFICATIONS, HPLC

Monograph
100F [2012]
Monograph 88
[2006]
Monograph 62
[1995]
Supplement 7
[1987]

ACGIH (American Conference of Governmental Industrial Hygienists)

IARC (International Agency for Research on Cancer)

NTP (National Toxicology Program)

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

Reproductive toxicity Suspected of damaging fertility or the unborn child

Reproductive Effects: No information available

Developmental Effects: Possible risk of harm to the unborn child

Teratogenic Effects: No information available

Specific Target Organ Toxicity

STOT - single exposure Respiratory system. central nervous system.

STOT - repeated exposure No information available.

Target Organs: Skin. Central nervous system. Peripheral nervous system. Kidneys. Liver.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Ecotoxicity effects: Aquatic environment.

Acetone - 67-64-1

Freshwater Fish Species Data: 4.74 - 6.33 mL/L LC50 Oncorhynchus mykiss 96 h 1

8300 mg/L LC50 Lepomis macrochirus 96 h 1

6210 - 8120 mg/L LC50 Pimephales promelas 96 h static 1

Water Flea Data: 10294 - 17704 mg/L EC50 Daphnia magna 48 h

12600 - 12700 mg/L EC50 Daphnia magna 48 h

Benzene - 71-43-2

Freshwater Algae Data: 29 mg/L EC50 Pseudokirchneriella subcapitata 72 h

Freshwater Fish Species Data: 10.7 - 14.7 mg/L LC50 Pimephales promelas 96 h flow-through 1 5.3 mg/L LC50

Oncorhynchus mykiss 96 h flow-through 1 22.49 mg/L LC50 Lepomis macrochirus 96 h static 1 28.6 mg/L LC50 Poecilia reticulata 96 h static 1 22330 - 41160 μ g/L LC50 Pimephales promelas 96 h static 1 70000 - 142000 μ g/L LC50 Lepomis

11 / 18

macrochirus 96 h static 1

Water Flea Data: 8.76 - 15.6 mg/L EC50 Daphnia magna 48 h 10 mg/L EC50 Daphnia magna 48 h

Formaldehyde - 50-00-0

Freshwater Fish Species Data: 0.032 - 0.226 mL/L LC50 Oncorhynchus mykiss 96 h flow-through 1

100 - 136 mg/L LC50 Oncorhynchus mykiss 96 h static 1

22.6 - 25.7 mg/L LC50 Pimephales promelas 96 h flow-through 1

23.2 - 29.7 mg/L LC50 Pimephales promelas 96 h static 1 1510 µg/L LC50 Lepomis macrochirus 96 h static 1

41 mg/L LC50 Brachydanio rerio 96 h static 1

Water Flea Data: 11.3 - 18 mg/L EC50 Daphnia magna 48 h

2 mg/L LC50 Daphnia magna 48 h

Persistence and degradability: No information available

Product code: HP402 Product name: ACETONE, EXCEEDS

A.C.S. SPECIFICATIONS, HPLC

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Disposal Methods

Waste from residues / unused products:

Waste must be disposed of in accordance with Federal, State and Local regulation.

Contaminated packaging:

Empty containers should be taken for local recycling, recovery or waste disposal

Components	CAS-No.	RCRA - F Series Wastes	RCRA - K Series Wastes	RCRA - P Series Wastes	RCRA - U Series Wastes
Acetone	67-64-1	None	None	None	U002 Ignitable waste
Benzene	71-43-2	None	None		U019 ignitable waste, toxic waste
Formaldehyde	50-00-0	None	None	None	U122

14. TRANSPORT INFORMATION

DOT

UN-No: UN1090 Proper Shipping Name: Acetone

Hazard Class: 3

Subsidiary Class No information available

Packing group:

Emergency Response Guide No information available

Number

Marine PollutantNo data availableDOT RQ (lbs):5000 lbs./2270 kgSpecial ProvisionsNo Information available

Symbol(s): [DOT]: (R5) - Identifies a material that is a hazardous substance that has a

reportable quantity (RQ) of 5000 pounds (2270 Kilograms).

Description: UN1090,Acetone ,3,,PG II

TDG (Canada)

UN-No: UN1090 Proper Shipping Name: Acetone

Hazard Class: 3

Subsidiary Risk: No information available

Packing Group:

Marine Pollutant

No Information available

Description:

ACETONE,3,UN1090,PG II

ADR

UN-No: UN1090 Proper Shipping Name: Acetone

Hazard Class: 3
Packing Group: ||

Subsidiary Risk: No information available Description: UN1090 Acetone,3,II

IMO / IMDG

UN-No: UN1090

Proper Shipping Name: Acetone (Acetone solutions)

Hazard Class: 3

Subsidiary Risk: No information available

Packing Group:

Marine Pollutant No information available

EMS: F-E

RID

UN-No: UN1090 Proper Shipping Name: Acetone

Hazard Class: 3
Subsidiary Risk: 3
Packing Group: ||

Description: UN1090 Acetone,3,II,RID

ICAO

UN-No: UN1090 Proper Shipping Name: Acetone

Hazard Class: 3

Subsidiary Risk: No information available

Packing Group:

Description: Acetone,3,UN1090,PG II

IATA

UN-No: UN1090 Proper Shipping Name: Acetone

Hazard Class: 3

Subsidiary Risk: No information available

Packing Group: II ERG Code: 3H

Special ProvisionsNo information available **Description:**UN1090,Acetone,3,PG II

15. REGULATORY INFORMATION

International Inventories

Components	CAS-No.	U.S. TSCA	KOREA KECL	Philippines (PICCS)	Japan ENCS	CHINA	Australia (AICS)	EINECS-No.
Acetone	67-64-1	Present (ACTIVE)	Present KE-29367	Present	Present (2)-542	Present	Present	Present 200-662-2
Benzene	71-43-2	Present(ACTI VE)	Present KE-02150	Present	Present (3)-1	Present	Present	Present 200-753-7
Formaldehyde	50-00-0	Present(ACTI VE)	Present KE-17074	Present	Present (2)-482	Present	Present	Present 200-001-8

U.S. Regulations

Acetone

Massachusetts RTK: Present

New Jersey RTK Hazardous Substance List: Present (sn 006)

New Jersey - Discharge Prevention - List of Hazardous Substances: Present

Pennsylvania RTK: Environmental hazard

Pennsylvania RTK - Environmental Hazard List Present

Minnesota - Hazardous Substance List: Present

New York Release Reporting - List of Hazardous Substances:

= 1 lb RQ (land/water)

13 / 18

= 5000 lb RQ (air)

Louisana Reportable Quantity List for Pollutants: Listed
California Directors List of Hazardous Substances: Present
FDA - Direct Food Additives 21 CFR 173.210

FDA - 21 CFR - Total Food Additives 173.210 175.105 175.320 176.180 176.300 177.2600 73.1 73.30 73.345 73.615

Benzene

Massachusetts RTK: Present

New Jersey RTK Hazardous Substance List: 0197

New Jersey (EHS) List: 0197 500 lb TPQ

New Jersey - Discharge Prevention - List of Hazardous Substances: Present

Pennsylvania RTK: Environmental hazard

Present

Special hazardous substance

Pennsylvania RTK - Environmental Hazard List Present
Pennsylvania RTK - Special Hazardous Substances Present

Michigan - Critical Materials List: Present Minnesota - Hazardous Substance List: Present

New York Release Reporting - List of Hazardous Substances:

10 lb RQ 1 lb RQ

Connecticut - Carcinogenic Substances: Present

Louisana Reportable Quantity List for Pollutants: 10lbfinal RQreceives an adjustable RQ of 10 lbs based on potential carcinogenicity in

August 14, 1989 final rule

4.54kgfinal RQreceives an adjustable RQ of 10 lbs based on potential carcinogenicity in August 14, 1989 final rule

California Directors List of Hazardous Substances: Present FDA - 21 CFR - Total Food Additives 172.560, 175.105

Formaldehyde

Massachusetts RTK: Present

Massachusetts EHS: carcinogen; extraordinarily hazardous New Jersey RTK Hazardous Substance List: 0946

New Jersey (EHS) List: 0946 500 lb TPQ

New Jersey - Discharge Prevention - List of Hazardous Substances: Present

New Jersey TCPA - EHS: 175lbTQ

15000lbTQ

Pennsylvania RTK: Environmental hazard

Special hazardous substance

Pennsylvania RTK - Environmental Hazard List Present
Pennsylvania RTK - Special Hazardous Substances Present

Michigan PSM HHC: = 1000 lb TQ

Minnesota - Hazardous Substance List: Present

New York Release Reporting - List of Hazardous Substances:

100 lb RQ 1 lb RQ

Louisana Reportable Quantity List for Pollutants: 100lbfinal RQ

45.4kgfinal RQ

California Directors List of Hazardous Substances: Present FDA - Direct Food Additives 21 CFR 173.340

FDA - 21 CFR - Total Food Additives 173.340 175.105 175.210 175.300 176.170 176.180 176.200 177.1200 177.2410

178.3120 573.460

California Prop. 65: Safe Drinking Water and Toxic Enforcement Act of 1986.

Chemicals Known to the State of California to Cause Cancer:

MARNING: This product can expose you to chemicals including (see table below) which is (are) known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

Chemicals Known to the State of California to Cause Reproductive Toxicity:

MARNING: This product can expose you to chemicals including (see table below) which is (are) known to the State of California to cause birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.

Components	CAS-No.	Carcinogen	Developmental Toxicity	Reproductive	Female Reproductive Toxicity:
Acetone	67-64-1	Not Listed	Not Listed	Not Listed	Not Listed
Benzene	71-43-2	carcinogen	developmental toxicity	male reproductive toxicity	Not Listed
Formaldehyde	50-00-0	carcinogen	Not Listed	Not Listed	Not Listed

CERCLA/SARA

Components	CAS-No.	CERCLA - Hazardous Substances and their Reportable Quantities	Section 302 Extremely Hazardous Substances and TPQs	Section 302 Extremely Hazardous Substances and RQs	Section 313 - Chemical Category	Section 313 - Reporting de minimis
Acetone	67-64-1	5000 lb final RQ 2270 kg final RQ	None	None	None	None
Benzene	71-43-2	10 lb final RQ 4.54 kg final RQ	None	None	None	0.1 % de minimis concentration
Formaldehyde	50-00-0		100 lb EPCRA RQ	None		0.1 % de minimis concentration

U.S. TSCA

Components		TSCA Section 5(a)2 - Chemicals With Significant New Use Rules (SNURS)	TSCA 8(d) -Health and Safety Reporting
Acetone	67-64-1	Not Applicable	Not Applicable
Benzene	71-43-2	Not Applicable	Not Applicable
Formaldehyde	50-00-0	Not Applicable	Not Applicable

Canada

WHIMIS 2015 - GHS Classifications

WHMIS 2015 Hazard Classification Information:

Component Acetone 67-64-1 (99-100.5)

Benzene 71-43-2 (0-0.003)

Formaldehyde 50-00-0 (0-0.002)

Product code: HP402

WHMIS 2015 Hazard Classification

Flammable liquids - Category 2: H225 Highly flammable liquid and vapour.; Serious Eye Damage/Eye Irritation - Category 2A: H319 Causes serious eye irritation.

Flammable liquids - Category 2: H225 Highly flammable liquid and vapour.; Skin corrosion/irritation - Category 2: H315 Causes skin irritation.; Serious Eye Damage/Eye Irritation - Category 2: H319 Causes serious eye irritation.; Germ cell mutagenicity - Category 1B: H340 May cause genetic defects.; Carcinogenicity - Category 1A: H350 May cause cancer.; Specific target organ toxicity - Repeated exposure - Category 1: H372 Causes damage to organs through prolonged or repeated exposure.; Aspiration hazard - Category 1: H304 May be fatal if swallowed and enters airways

Flammable gases - Category 1: H220 Extremely flammable gas.; Flammable liquids - Category 3: H226 Flammable liquid and vapour. (solution, 37%); Corrosive to Metals - Category 1: H290 May be corrosive to metals. (solution, 37%); Acute toxicity - Oral -Category 4: H302 Harmful if swallowed. (solution, 37%); Acute toxicity - Dermal - Category 3: H311 Toxic in contact with skin. (solution, 37%); Acute toxicity - Inhalation - Category 2: H330 Fatal if inhaled.; Skin corrosion/irritation - Category 2: H315 Causes skin irritation. (solution, 37%); Serious Eye Damage/Eye Irritation - Category 1: H318 Causes serious eye damage. (solution, 37%); Serious Eye Damage/Eye Irritation - Category 2: H319 Causes serious eye irritation.; Skin sensitizers - Category 1A: H317 May cause allergic skin reaction. (solution, 37%); Germ cell mutagenicity - Category 2: H341 Suspected of causing genetic defects.; Carcinogenicity - Category 1A: H350 May cause cancer.; Reproductive Toxicity - Category 1: H360 May damage fertility or the unborn child. (solution, 37%; contains 16% of a substance that is toxic to reproduction (Methyl alcohol)); Specific target organ toxicity - Single exposure - Category 2: H371 May cause damage to organs. (solution, 37%); Specific target organ toxicity - Single exposure - Category 3: H335 May cause respiratory irritation.; Specific target organ toxicity - Single

exposure - Category 3: H336 May cause drowsiness or dizziness. (solution, 37%)

Canada Hazardous Products Regulation This product has been classified according to the hazard criteria of the HPR (Hazardous Products Regulation) and the SDS contains all of the information required by the HPR

WHMIS 1988 Hazard Class

B2 Flammable liquid D2B Toxic materials

Components Acetone Benzene Formaldehyde

WHMIS 1988 B2 D2B B2,D2A,D2B A B1 D1A D2A D2B

B3 D1A D2A D2B E regulated under Formol

Canada Controlled Products Regulation:

This product has been classified according to the hazard criteria of the CPR (Controlled Products Regulation) and the MSDS contains all of the information required by the CPR.

Components	WHMIS Ingredient Disclosure List -
Acetone	1 %
Benzene	0.1 %
Formaldehyde	0.1 %

Inventory

Components	CAS-No.	Canada (DSL)	Canada (NDSL)
Acetone	67-64-1	Present	Not Listed
Benzene	71-43-2	Present	Not Listed
Formaldehyde	50-00-0	Present	Not Listed

	Ta . a	I
Components	CAS-No.	CEPA Schedule I - Toxic Substances
Acetone	67-64-1	Not listed
Benzene	71-43-2	Present
Formaldehyde	50-00-0	Present
Components	CAS-No.	CEPA - 2010 Greenhouse Gases Subject
		to Mandatory Reporting
Acetone	67-64-1	Not listed
Benzene	71-43-2	Not listed
Formaldehyde	50-00-0	Not listed

EU Classification

EU GHS - SV - CLP 1272/2008

Product code: HP402

Components	CAS-No.	EU GHS - SV - CLP (1272/2008)
Acetone	67-64-1	
Benzene	71-43-2	Flammable liquids - Flam. Liq. 2: H225 Highly flammable liquid and vapour.; Skin corrosion/irritation - Skin Irrit. 2: H315 Causes skin irritation.; Serious Eye Damage/Eye Irritation - Eye Irrit. 2: H319 Causes serious eye irritation.; Germ cell mutagenicity - Muta. 1B: H340 May cause genetic defects.; Carcinogenicity - Carc. 1A: H350 May cause cancer.; Specific target organ toxicity - Repeated exposure - STOT RE 1: H372 Causes damage to organs through prolonged or repeated exposure. (No information to prove exclusion of certain routes of

Product name: ACETONE, EXCEEDS A.C.S. SPECIFICATIONS, HPLC

		exposure); Aspiration hazard - Asp. Tox. 1: H304 May be fatal if swallowed and enters airways.601-020-00-8
Formaldehyde	50-00-0	

EU - CLP (1272/2008)

R-phrase(s)

R11 - Highly flammable.

R36 - Irritating to eyes.

R66 - Repeated exposure may cause skin dryness or cracking.

R67 - Vapors may cause drowsiness and diziness.

S -phrase(s)

S 9 - Keep container in a well-ventilated place.

S16 - Keep away from sources of ignition - No smoking.

S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Components	CAS-No.	Classification	Concentration Limits:	Safety Phrases
Acetone	67-64-1	F; R11 Xi; R36 R66 R67	No information	S2 S9 S16 S26
Benzene	71-43-2	F; R11 Xi; R36/38 Carc.Cat.1; R45 Muta.Cat.2; R46 T; R48/23/24/25 Xn; R65	No information	S53 S45
Formaldehyde	50-00-0		0.2%<=C<1% Xi;R43 1%<=C<5% Xn;R40-43 25%<=C T;R23/24/25-34-40-43 5%<=C<25% Xn;R20/21/22-36/37/3 8-40-43	S(1/2)-S26-S36/37/39- S45-S51

The product is classified in accordance with Annex VI to Directive 67/548/EEC

Indication of danger:

Xi - Irritant.

F - Highly flammable.





16. OTHER INFORMATION

Preparation Date: 1/15/2014

Revision Date: 4/04/2018 Sonia Owen Prepared by:

Disclaimer: All chemicals may pose unknown hazards and should be used with caution. This

Safety Data Sheet (SDS) applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this SDS. The physical properties reported in this SDS are obtained from the literature and do not constitute product specifications. Information contained herein does not constitute a warranty, whether expressed or implied, as to the safety, merchantability or fitness of the goods for a particular purpose. Spectrum Chemicals & Laboratory Products, Inc. assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this SDS is based on technical data judged to be reliable, Spectrum assumes no responsibility for the completeness or accuracy of the information contained herein.

End of Safety Data Sheet

Product code: HP402

Product name: ACETONE, EXCEEDS A.C.S. SPECIFICATIONS, HPLC GRADE